

Liberty's Choice Sealer 25

Concrete Sealer 25

TECHNICAL DATA SHEET

DESCRIPTION

Liberty's Choice Sealer 25 is a 25% solids tough, clear, pure acrylic, non-yellowing sealer formulated for all types of cured concrete. Especially decorative, stained, stamped or colored concrete and provides a high gloss, wet-looking finish. **Liberty's Choice Sealer 25** is solvent-based for lasting beauty and durability and will help protect your concrete against weathering and erosion.

USES

Liberty's Choice Sealer 25 provides a protective and decorative look on all types of horizontal concrete surfaces.

FEATURES

- Clear
- High Gloss
- Wet Look
- Film Forming
- Solvent-Based
- Pure Acrylic
- Water repellent
- Breathable
- Non-yellowing
- Chemical Resistant
- Protects Surface
- Reduces Mold and Fungus Growth

SURFACE PREPARATION

Clean dirt, wax, grease, oil and other contaminants from the surface of concrete with a pressure washer. Be sure to remove any foreign coating unless previous coating is same or similar water-based sealer. Make sure the surface is clean, dry and sound. Clean oily concrete with a cleaner/degreaser. Use a bristle brush for heavily oiled spots. If surface is slick, etch with an etcher. Rinse well with a pressure washer. Allow 24 hours to dry. Apply only when surface and air temperatures are above 50° F and below 90° F. Do not apply to excessively hot surfaces as rapid drying may cause streaking to form.

TECHNICAL

ASTM C309 Type 1 AB, ASTM C1315 Type 1 ABC
25% Solids

PLACING

Perform test to ensure compatibility. Brush may be used where roller won't reach. Do not pour directly from can to concrete. Apply evenly from can or other metal container with solvent resistant roller. Use a long nap roller for exposed aggregate, a medium nap roller for textured surfaces and a short nap roller for smooth surfaces. Keep roller soaked. Wait until the surface is tack-free before applying a second coat by cross-rolling perpendicular to the first coat. Do not thin product. Foot traffic should be avoided for 4 hours. Vehicle traffic should be avoided for 48 hours. Do not apply if rain is imminent. Cooler temperatures or increased humidity will slow the drying time.

COVERAGE

Smooth Troweled:	300 ft ² per gallon
Textured or Stamped:	200 ft ² per gallon
Broom Swept:	200 ft ² per gallon
Exposed Aggregate:	100 ft ² per gallon

CLEANUP

Clean up immediately with aromatic solvent such as xylene.

DRY TIME

Foot traffic should be avoided for 4 hours. Vehicle traffic should be avoided for 48 hours. Cooler temperatures or increased humidity will slow the dry.

MAINTENANCE


Clean sealed surface with water only. Re-seal surface every two years or as needed to prevent buildup of sealer.

STORAGE

Recommended shelf life is one year.

SLIP RESISTANCE

For additional slip resistance, apply one coat of sealer. Mix grip additive into sealer and apply with second coat.



Cincinnati, OH: 513-489-9111 Dayton, OH: 937-866-9111
Bond Hill, OH: 513-651-9111 Columbus, OH: 614-224-9111
Erlanger, KY: 859-341-9111 Lexington, KY: 859-254-9111

Liberty's Choice Sealer 25

Concrete Sealer 25

PHYSICAL PROPERTIES

Appearance	Clear Liquid
pH	None
Specific Gravity	.93 g/cc
Lbs/Gal	7.8
Min. Temp	50 degrees
Water Resistance	Excellent
Viscosity	75 centipoise
VOC	<700 g/L
Flash Point	106 degrees F
DOT	Non-Regulated Material

CURE TIME

Dry to Touch	2 hours
Recoat	2 hours
Foot Traffic	4 hours
Wheel Traffic	48 hours

CONTAINER SIZES

1 gallon	(3.8 Liters)
5 gallon	(18.93 Liters)
55 gallon	(208.2 Liters)

HMIS

Health	2	Flammability	2
Reactivity	0	Protection	B

LIMITATIONS

Always test a small area for compatibility before proceeding.

Not recommended for clay brick, interior applications, natural stone, travertine, painted surfaces, tile, epoxy set stone, vertical surfaces, areas prone to drainage issues, or any surface not specifically recommended.

WARRANTY

Since Manufacturer has no control over handling, use or storage; no guarantee expressed or implied, is offered. The suitability of the product for use shall be solely up to the user. Manufacturer retains the right to venue.

WARNINGS

Danger: Flammable liquid and vapor. May be fatal if swallowed and enters airway. Causes skin irritation. Causes serious eye irritation. toxic if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. May cause genetic defects. Suspected of causing cancer. May damage fertility or the unborn child. May cause damage to organs (liver, kidney, central nervous system) through prolonged exposure. Toxic to aquatic life.

Precaution: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist/vapors/spray. Wear eye protection. Use only outdoors or in a well-ventilated area. Do not eat, drink, or smoke while using product. KEEP OUT OF REACH OF CHILDREN.


FIRST AID

IF SWALLOWED: Do NOT induce vomiting. Immediately call a poison center or doctor/physician. **IF ON SKIN (or hair):** Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call poison center or doctor/physician. **IF IN EYE:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire use dry sand, dry chemical, or alcohol-resistant foam for extinguishing.

MANUFACTURER/TECHNICAL SERVICE

Exclusively manufactured for Janell Inc. by **CLEMONS CONCRETE COATINGS**

Contact your Janell representative for the most current product information. Always read and follow the warnings and instructions on the most current technical data sheets.



Cincinnati, OH: 513-489-9111 Dayton, OH: 937-866-9111
 Bond Hill, OH: 513-651-9111 Columbus, OH: 614-224-9111
 Erlanger, KY: 859-341-9111 Lexington, KY: 859-254-9111