

# Refresher Solution

## Reactivation Cleaner

## TECHNICAL DATA SHEET

### DESCRIPTION

**Refresher Solution Reactivation Cleaner** is an aggressive solvent specially blended to re-melt sealer for cleaning sealer application tools. Spray application of **Refresher Solution Reactivation Cleaner** to cured acrylic sealers will allow the release of trapped moisture and air.

### USES

**Refresher Solution Reactivation Cleaner** is for use on solvent-based acrylic sealers, solvent-based penetrating sealers and as a cleaner for tools. **Refresher Solution Reactivation Cleaner** can be used to remelt thick films and bubbles.

### FEATURES

- Refreshes Sealer
- Eliminates Hazing
- Acts Fast
- Cuts Through Film Build Up
- Cleans Tools

### SURFACE PREPARATION

Clean surface with water to remove dirt and debris. Make sure that the surface is clean and dry prior to applying **Refresher Solution Reactivation Cleaner**.

### PLACING

Best results are achieved when the wash is done on a cool, overcast day. Avoid applying **Refresher Solution Reactivation Cleaner** in direct sunlight or hot weather. **Refresher Solution Reactivation Cleaner** should be applied with a solvent-resistant pump sprayer. It may be necessary to perform several applications approximately 2-3 minutes apart to allow full penetration. The film has not been completely melted until the surface darkens from solvent penetration. Hold sprayer tip 8" from surface during application. Avoid creating large puddles. Do not thin. When using a roller, pour the solvent into a metal or solvent-resistant paint tray and use a short-nap, solvent-resistant roller to apply **Refresher Solution Reactivation Cleaner** to the areas of sealer to be treated at a coverage rate of approximately 200 ft<sup>2</sup> per gallon. Use steady, even strokes to apply the solvent but do not "over roll" back and forth aggressively as this can cause bubbling. After a few minutes, **Refresher Solution Reactivation Cleaner** will re-wet the sealer, turning it back to its original liquid form.

**Refresher Solution Reactivation Cleaner** used as a cleaner, tools should be soaked briefly, wiped clean and allowed to dry.

### COVERAGE


Treats approximately 200 ft<sup>2</sup> per gallon

### DRY TIME

Suitable for foot traffic in 4 hours and vehicle traffic in 48 hours. Additional coats should be applied immediately after previous coat is dry to the eye.

### STORAGE

Recommended shelf life is one year.



Cincinnati, OH: 513-489-9111      Dayton, OH: 937-866-9111  
 Bond Hill, OH: 513-651-9111      Columbus, OH: 614-224-9111  
 Erlanger, KY: 859-341-9111      Lexington, KY: 859-254-9111

# Refresher Solution

## Reactivation Cleaner

### PHYSICAL PROPERTIES

Appearance	Clear Liquid
pH	None
Specific Gravity	.87 g/cc
Lbs/Gal	7.35
Min. Temp	50 degrees
Water Resistance	N/A
Viscosity	Not determined
VOC	<870 g/L
Flash Point	45° F
DOT	UN1263, Paint Related Material, 3, PG II

### CURE TIME

Dry to Touch	2 hours
Foot Traffic	4 hours
Wheel Traffic	48 hours

### CONTAINER SIZES

1 gallon (3.8 Liters)
5 gallon (18.93 Liters)
55 gallon (208.2 Liters))

### HMIS

Health	2	Flammability	3
Reactivity	0	Protection	B

### LIMITATIONS

Not for use with water based products. Not recommended for interior applications.

### WARRANTY

Since Manufacturer has no control over handling, use or storage; no guarantee expressed or implied, is offered. The suitability of the product for use shall be solely up to the user. Manufacturer retains the right to venue.

### WARNINGS

**Danger:** Flammable liquid and vapor. Toxic if swallowed. May be fatal if swallowed and enters airway. Causes skin irritation. Causes serious eye irritation. May be harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. May cause genetic defects. Suspected of causing cancer. may damage fertility or the unborn child. May cause damage to organs (liver, kidney, central nervous system) through exposure. Toxic to aquatic life.

**Precaution:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Keep container tightly closed. Do not breathe mist/vapors/spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Use personal protective equipment as required. **KEEP OUT OF REACH OF CHILDREN.**


### FIRST AID

**IF SWALLOWED:** Do NOT induce vomiting. Immediately call a poison center or doctor/physician. **IF ON SKIN (or hair):** Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. **IF INHALED:** Remove person to fresh air and keep at rest in a position comfortable for breathing. Call poison center or doctor/physician **IF IN EYE:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire use dry sand, dry chemical, or alcohol-resistant foam for extinguishing.

### MANUFACTURER/TECHNICAL SERVICE

Exclusively manufactured for Janell Inc. by **CLEMONS CONCRETE COATINGS**

Contact your Janell representative for the most current product information. Always read and follow the warnings and instructions on the most current technical data sheets.



Cincinnati, OH: 513-489-9111      Dayton, OH: 937-866-9111  
 Bond Hill, OH: 513-651-9111      Columbus, OH: 614-224-9111  
 Erlanger, KY: 859-341-9111      Lexington, KY: 859-254-9111